



VA 30 SH

Electric

Article code	Power
707199	400V, 50HZ

Key features	
Wattage/HP	7,5Kw
Working width	30cm/12"
Distance to wall	9cm/3.5"
Depth hard concrete	7mm/.27"
Depth softer concrete	10mm/.40"
Production/h	50-55m2/540sqf
Standard cutters	Octagonal carbide

Physical parameters		
Weight kg/lbs	707199	305.4/673
Dimensions cm/inch	135x56x109/53x22x43	

Field of application	
<p>Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:</p> <ul style="list-style-type: none"> Asphalt and cast asphalt surfaces Concrete and cement, synthetic stone, floor tiles Screeds of cement, wood cement, ceramic etc. Natural stone Metals Thermoplastic materials 	
<p>Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:</p> <ul style="list-style-type: none"> Latex, rubber, soft plastics and foam materials Wood, carpets and woven materials 	



VA 30 SH

Diesel with hydraulic traction



Article code	Power
707200	Diesel

Key features	
Wattage/HP	5,6 Kw
Working width	30 cm / 12"
Distance to wall	9 cm / 3.5"
Depth hard concrete	7 mm / .27"
Depth softer concrete	10 mm / .40"
Production/h	50-55 m2 / 540sqf
Standard cutters	Octagonal carbide

Physical parameters	
Weight kg/lbs	273 Kg / 602 lbs
Dimensions cm/inch	135×56×109 / 53×22×43

Field of application	
<p>Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:</p>	<ul style="list-style-type: none"> • Asphalt and cast asphalt surfaces • Concrete and cement, synthetic stone, floor tiles • Screeds of cement, wood cement, ceramic etc. • Natural stone • Metals • Thermoplastic materials
<p>Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:</p>	<ul style="list-style-type: none"> • Latex, rubber, soft plastics and foam materials • Wood, carpets and woven materials



VA 30 SH

Diesel with electrostart

Article code	Power
707532	Diesel electrostart

Key features	
Wattage/HP	7,5Kw
Working width	30cm/12"
Distance to wall	9cm/3.5"
Depth hard concrete	7mm/.27"
Depth softer concrete	10mm/.40"
Production/h	50-55m2/540sqf
Standard cutters	Octagonal carbide

Physical parameters

Weight kg/lbs	305.4/673
Dimensions cm/inch	135×56×109/53×22×43

Field of application

Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:

- Asphalt and cast asphalt surfaces
- Concrete and cement, synthetic stone, floor tiles
- Screeds of cement, wood cement, ceramic etc.
- Natural stone
- Metals
- Thermoplastic materials

Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:

- Latex, rubber, soft plastics and foam materials
- Wood, carpets and woven materials

VA 30 SH

Gasoline with hydraulic traction



Article code **Power**

707533 Gasoline

Key features

Wattage/HP 8,2 Kw

Working width 30 cm / 12"

Distance to wall 9 cm / 3.5"

Depth hard concrete 7 mm/.27"

Depth softer concrete 10 mm/.40"

Production/h 50-55 m2 / 540sqf

Standard cutters Octagonal carbide

Physical parameters

Weight kg/lbs 310 Kg / 683 lbs

Dimensions cm/inch 135×56×109 / 53×22×43

Field of application













Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:

- Asphalt and cast asphalt surfaces
- Concrete and cement, synthetic stone, floor tiles
- Screeds of cement, wood cement, ceramic etc.
- Natural stone
- Metals
- Thermoplastic materials

Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:

- Latex, rubber, soft plastics and foam materials
- Wood, carpets and woven materials

Spare parts

Octagonal cutters for VA 30 S / VA 30 SH	Octagonal cutters set 701836		Complete drum 701691		<p>Application: With tungsten carbide inserts, for roughening concrete and asphalt, for removing old coatings</p> <p>One set contains: 4 flail shafts, 5.0kg washers, 72 pcs octagonal cutters large</p>
Bihexagonal cutters for VA 30 S / VA 30 SH	Hexagonal cutters set 706691		Complete drum 706566		<p>Application: With tungsten carbide inserts, for roughening concrete and asphalt, for removing old coatings</p> <p>One set contains: 4 flail shafts, 5.0kg washers, 72 pcs bihexagonal cutters large</p>
Beam cutters for VA 30 S / VA 30 SH	Beam cutters set 701839		Complete drum 701694		<p>Application: For removing road markings and paint from asphalt and concrete, and for work on large steel structures with only a slight change of the surface structure</p> <p>One set contains: 4 flail shafts, ca. 5.8kg washers ca. 11.6kg beam cutters large</p>
Milling cutters 19mm for VA 30 S / VA 30 SH	Milling cutters set 701841		Complete drum 701696		<p>Application: For removing and stripping thermoplastic and cold plastic coatings and markings</p> <p>One set contains: 4 flail shafts, 6.0kg washers, 24 pcs milling cutters large</p>
Milling cutters 39mm for VA 30 S / VA 30 SH	Milling cutters set 701840		Complete drum 701695		<p>Application: For removing and stripping thermoplastic and cold plastic coatings and markings</p> <p>One set contains: 4 flail shafts, ca. 6.0kg washers, 12 pcs milling cutters large</p>
Round cutter for VA 30 S / VA 30 SH	Round cutter set 701842		Complete drum 701697		<p>Application: With tungsten carbide inserts, for roughening concrete and asphalt, for removing old coatings</p> <p>One set contains: 4 flail shafts, 5.9kg washers, 56 pcs round cutters large</p>