


401 DRY - INDUSTRIAL SINGLE PHASE



CERAMICS AND POTTERY INDUSTRIES



ELECTRONICS



- ✓ High efficiency filtration
- ✓ Compact and mobile
- ✓ Complete steel construction
- ✓ Easy to handle
- ✓ Accessory kit included

- ✓ Possibility of using filter bags to safely dispose of the sucked material
- ✓ Absolute class H filter included
- ✓ Electric plug for power tools connection
- ✓ Three levels of filtration with disposal bag, class M bag filter and class H cartridge filter



DEMONSTRATION
& HOW-TO VIDEOS





SUCTION UNIT

Voltage	V - Hz	230 - 50
Power	kW	1,15
Max water lift	mmH ₂ O	2.500
Max air flow	m ³ /h	180
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	74



FILTER UNIT

Filter Type		Cartridge
Surface - Diameter	cm ² -mm	6.000 - 360
Material - Efficiency	IEC 60335-2-69	Polyester - M PTFE
Air load on filter	m ³ /m ² /h	300
Cleaning system		Dustop



COLLECTION UNIT

Discharge system		
Capacity	lt	13



VOLUME

Dimensions	cm	46x48x85h
Weight	kg	25