

DM3 EL LP - INDUSTRIAL SINGLE PHASE



CEMENT



SURFACE PREPARATION



- ✓ Largest surface filter in its category
- ✓ Integrated filter cleaning system
- ✓ Three powerful by pass motors with independent cooling
- ✓ Compact and mobile
- ✓ Full customization for specific needs
- ✓ Disposable bags for hazardous dusts safe disposal
- ✓ Adjustable height to facilitate transport on vehicles
- ✓ Complete steel construction
- ✓ Easy to handle
- ✓ Easy to clean and to maintain



DEMONSTRATION
& HOW-TO VIDEOS





SUCTION UNIT

Voltage	V - Hz	230 - 50
Power	kW	3,45
Max water lift	mmH ₂ O	2.500
Max air flow	m ³ /h	540
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	76



FILTER UNIT

Filter Type		Star
Surface - Diameter	cm ² -mm	30.000 - 500
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Air load on filter	m ³ /m ² /h	180
Cleaning system		Manual



COLLECTION UNIT

Discharge system		Endless Bag
------------------	--	-------------



VOLUME

Dimensions	cm	80x66x155h
Weight	kg	70